



Karbonathärte in ° dH	Empfohlene Verschnitteinstellung	Filterkapazität in Litern			
		PC15 (Q0025.1)	PC30 (Q0026.1)	PC50 (Q0030.1)	PC110 (Q0041.1)
4		kein Wasserfilter erforderlich			
5		kein Wasserfilter erforderlich			
6	70%	4766	7917	13458	22760
7	70%	4569	7589	12902	21819
8	70%	3574	5938	10094	17070
9	70%	3177	5278	8972	15174
10	60%	2408	4000	6800	11500
11	60%	2189	3636	6182	10455
12	50%	1738	2887	4908	8300
13	50%	1604	2665	4530	7661
14	50%	1490	2474	4207	7114
15	50%	1390	2310	3926	6640
16	50%	1303	2165	3681	6225
17	50%	1227	2038	3464	5859
18	50%	1159	1925	3272	5533
19	40%	970	1612	2740	4634
20	40%	922	1531	2603	4402
21	40%	878	1458	2479	4193
22	40%	838	1392	2366	4002
23	40%	802	1332	2264	3828
24	40%	768	1276	2169	3669
25	40%	737	1225	2083	3522
26	40%	709	1178	2002	3386
27	40%	683	1134	1928	3261
28	40%	658	1094	1859	3145
29	40%	636	1056	1795	3036
30	40%	615	1021	1735	2935
31	40%	595	988	1679	2840
32	40%	576	957	1627	2751
33	40%	559	928	1578	2668
34	40%	542	901	1531	2590
35	40%	527	875	1488	2516

Karbonathärte in ° dH	Empfohlene Verschnitteinstellung	Filterkapazität in Litern
		P03 (Q0022.1)
4	kein Wasserfilter erforderlich	
5	kein Wasserfilter erforderlich	
6	70%	25800
7	70%	22114
8	70%	19350
9	70%	17200
10	60%	13187
11	60%	11988
12	50%	9624
13	50%	8884
14	50%	8249
15	50%	7699
16	50%	7218
17	50%	6793
18	50%	6416
19	50%	6078
20	40%	5160
21	40%	4914
22	40%	4691
23	40%	4487
24	40%	4300
25	40%	4128
28	40%	3686
31	40%	3329
35	40%	2949

Wichtig:

Die Prozentangaben zur Verschnitteinstellung beinhalten die von Coffema empfohlene Erhöhung der Werte um 20 Prozentpunkte.